



Optics: Reflector  
Material: Aluminum  
Light Source: LED

## Specifications

Dimensions: L: 192mm W: 190mm H: 135mm  
Weight: 1,2kg  
Ingress protection: IP66  
Impact protection: IK10  
Protection class: I EU, IEC-EN60598



## APPLICATION AREAS

- Facade lighting

# SPECIFICATION

<b>Certified:</b>	No, luminaire complies with EN60598-2-3
<b>Light Source:</b>	LED
<b>Over voltage protection:</b>	4kV
<b>Non programmable version:</b>	1x9W
<b>Lumen output:</b>	3000K, 80lm/W
<b>Corrolated light temperature:</b>	3000K
<b>Color rendering index:</b>	CRI70
<b>SDCM:</b>	<5
<b>Lifetime according L80F10:</b>	100,000h (25 ° C)
<b>Lifetime according L70</b>	175,000h (25 ° C) IESNA LM80
<b>Operational temperature range:</b>	-40° to +30°C
<b>Driver/LEDs maintenance:</b>	Replaceable
<b>Mains voltage:</b>	220-240 V AC/50-60 Hz
<b>EMC:</b>	Driver/luminaire according EN55015,EN61000-2-3,EN61547
<b>Optics:</b>	Reflector
<b>Material:</b>	Aluminum. Stainless steel, glass
<b>WEight:</b>	1,2kg
<b>Color housing:</b>	Black (RAL9011)
<b>Monted installation cable:</b>	No

