


**FOLKE**

Optics: Reflector  
 Material: Aluminum  
 Light Source: 1-3pcs COBs

**Specification**

Diameter: 220mm H = 145mm L = 300mm(inc bracket)

Weight: 3,2kg

IP classification: IP65

IK classification: IK08

Protection class: I EU, IEC-EN60598

**Product description**

A neat "spotlight" floodlight with classic design which creates a pleasant welcoming atmosphere. Equipped with the latest technology. Light distribution delivered by reflectors with available glare protection for maximum performance and comfort.

Made from powder coated aluminum.  
 Reflector from anodized aluminum.  
 Delivered with mounted installation cable.

Cooling flanges are hidden and protected inside the housing.

**APPLICATION AREAS**

- Parks
- Residential areas
- Market places
- Buisness centers
- Parking lots

# SPECIFICATION

<b>Certified:</b>	No, luminaire complies with EN60598-2-3
<b>Futureproof for automated maintenance</b>	No
<b>Light Source:</b>	COB
<b>Optics/Angle beam:</b>	Reflector 15° standard (reflectors can be customized)
<b>Overvoltage protection:</b>	4Kv alt 10kV
<b>Programmable version:</b>	Inventronics EBS-series 10-40W (Protection class II)
<b>Non programmable versions:</b>	7W, 15W, 30W, (Protectionclass I & II)
<b>Light output:</b>	3000K, 125-150 lm/W
<b>CCT:</b>	3000K
<b>Color rendering Index:</b>	CRI70
<b>Lifetime according L80F10:</b>	100,000h (25° C)
<b>Lifetime according L70</b>	175,000h (25° C) IESNA LM80
<b>Operational temperature range:</b>	-40° to +30°C, LED module is protected from direct sunlight
<b>Driver/LEDs maintenance:</b>	
<b>Mains voltage:</b>	220-240 V AC/50-60 Hz
<b>EMC:</b>	Driver/luminaire according EN55015,EN61000-2-3,EN61547
<b>Material:</b>	Die-casted aluminum , polycarbonate
<b>Weight:</b>	3,2kg
<b>Color:</b>	RAL7016
<b>Mounted installation cable:</b>	Yes always, FQQ 3x1,5 / 2x1,5