

LED LINE



Optics: Reflector
Material: Aluminum
Light Source: LED

Specifications

Dimensions: Length:1000mm H = 120mm Width: 65mm

Weight: 3,2kg

Ingress protection: IP65

Impact protection: IK08

Protection class: I EU, IEC-EN60598



APPLICATION AREAS

- Facade lighting
- Sign lighting

SPECIFICATIONS

Certified:	No, luminaire complies with EN60598-2-3
Futureproof for automated maintenance:	No
Light source:	LED
Over voltage protection:	4kV
Programmable version:	N/A
Non programmable versions:	15W
Light output:	3000K, 100 lm/W
CCT:	3000K
Color rendering index:	CRI70
SDCM:	<5
Lifetime according to L80F10:	100,000h (25 °C)
Lifetime according to L70	175,000h (25 °C) IESNA LM80
Operating temperature:	-30° to +50°C, LED module is protected from direct sunlight
Driver/LED:s maintenance:	Non replaceable
Nominal voltage:	220-240 V AC/50-60 Hz
EMC:	Driver/luminaire according EN55015,EN61000-2-3,EN61547
Optics:	Reflectors
Material:	Aluminum, stainless steel
Weight:	3,2kg
Color:	RAL9006
Mounted installations cable:	Yes

