

ONYX 2



Optics: Lenses alt. Micro reflectors
Material: Aluminum
Light Source: LED

Characteristics

Dimensions: L=245mm B=90mm H=200mm

Weight 3,3kg
Ingress Protection IP65
Impact Protection IK10
Protection class II EU



APPLICATION AREAS

- Wallmounting



SPECIFICATION

Certified:	No, IP66, luminaire complies with EN60598-2-3
Futureproof automated maintenance:	No, not compatible with SSMS automated maintenance
Light Source:	LED
Overvoltage protection:	4kV
Output:	25W (15-30W adjustable)
Light output:	3000K 100-135 lm/W
Corrolated light temperature:	3000K
CRI:	CRI70
SDCM:	<5
Lifetime according L90:	100,000h
Lifetime according L80:	140,000h
Lifetime according L70:	175,000h
	IESNA LM80
Operational temperature range:	-40° to +30°C
Driver/LEDs maintenance:	Replaceable
Mains voltage:	220-240 V AC/50-60 Hz
EMC:	Driver/luminaire enligt EN55015,EN61000-2-3,EN61547
Optics:	Lenses, alt. Microreflectors
Material:	Housing from high pressured aluminum
Weight:	3,3kg
Housing color:	RAL 7016
Recommended mounting height:	2m-8m
Minimum mountin height:	2m (to ensure photobiological safety)
Mounted installationcable:	Yes
ScX:	0,02m2