

VINGA Medium & Large



Foundation
adapter /
Foundation



Optics: Reflector
Material: Aluminum, stainless steel, polycarbonate
Light Source: LED

Specification

Dimensions:

Medium Ø: 170mm H = 1080mm Round top H = 1000mm Flat top

Large: Ø: 200mm H = 1080mm Round top H = 1000mm Flat top

Weight: Medium = 7kg / Large = 9,7kg

Ingress Protection: IP54

Impact protection: IK08

Protection class: I / II EU, IEC-EN60598



APPLICATION AREAS

- Parks
- Urban areas
- Squares
- Buisness centers
- Parkinglots

SPECIFICATION

Certified:	No, bollard complies with EN60598-2-3
Futureproof for automated maintenance:	No
Light Source:	LED
Overvoltage protection:	4kV
Programmable version:	N/A
Non programmable versions:	7W
Light Output:	3000K, 125-150 lm/W
Correlated color temperature:	3000K
Color rendering index:	CRI70
SDCM:	>5
Service Life according L80F10:	100,000h (25 °C)
Service Life according L70	175,000h (25 °C) IESNA LM80
Operating temperature range:	-40° to +30°C
Driver/LEDs maintenance:	Replaceable
Mains voltage:	220-240 V AC/50-60 Hz
EMC:	Driver/bollard enlign EN55015,EN61000-2-3,EN61547
Optics:	Reflector
Material:	Aluminum, stainless steel, polycarbonate
Weight:	7kg /Medium – 9,7kg / Large
Color housing:	RAL7016

Mounted installation cable: Yes

